




Financial Bid

FOR 16 CLASS ROOMS					
SR. NO	SPECIFICATION	UNIT	QNTY	PRICE	AMOUNT
1	WALL PANELLING				
	Providing and fixing 70"x40" Acoustic panel made of 12mm thick waterproof ply and acrylic carpet with required frame made of 19mm thick water proof block board and hardware etc. as per given detail	pcs.	26		
2	LAMINATE PANELLING				
	Providing and fixing choukhat paneling all complete as per direction of E/I	M2	8.15		
3	FALSE CEILING				
a)	GYPSUM CEILING				
	Providing and fixing 12.5 mm thick fully Perforated Gypsum Board tile made from plasterboard having glass fibre conforming to IS: 2095 part I, of size 595x595 mm, having perforation of 9.7x9.7 mm at 19.4 mm c/c with center borders of 48 mm and the side borders of 30 mm, backed with non woven tissue on the back side, having an NRC (Noise Reduction Coefficient) of 0.79, with 50 mm resin bonded glass wool backing.	M2	8.71		
b)	GRID CEILING				
	The tiles should have Humidity Resistance , Light Reflectance >80%, Thermal Conductivity k = 0.052- 0.057 w/m K, Colour White, Fire Performance Class 0/Class1 (BS476 Pt:6&7) in module size of 600 X 600 X 12 mm, suitable for Green Building application, with Recycled content. The grid should be of "Armstrong" make with 24mm wide T - section flanges colour white having rotary stitching on all T sections i.e. the Main Runner, 1200 mm & 600 mm Cross Tees with a web height of 43, 35 and 30mm and a load carrying capacity of 23.78 Kgs/M2. The T Sections	SFT	454.52	0	0



NATIONAL UNIVERSITY OF STUDY & RESEARCH IN LAW, RANCHI

<p>have a Galvanizing of 120 grams per M2 & passed through 500 hrs of Salt test. The Tile & Grid system used together. Accessories manufactured and supplied by Armstrong World Industries consisting of M6 Anchor Fasteners with Vertical Hangers made of Galvanised steel of size 26 x 26 x 25 x 1.2mm with a Galvanised Thickness of 80gsm, A pre Straightened Hanger wire of dia – 2.68 mm of 1.83 m length., thickness of 80gsm and a tensile strength of 344-413 MPa, along with Adjustable hook clips of 0.8mm thick, galvanised spring steel for 2.68 mm with a minimum pull strength of 110 kg. The adjustable clip also consists of a 3.5 mm aquiline wire to be used with the main runner.</p>				
TOTAL				

